



DOMINATOR™ HIRO®



automatic
TECHNOLOGY

KEY FEATURES & INCLUDES:

- Opener with LED light
- 1400N Short-term peak force
- Soft Start / Soft Close
- Intelligent Safety System
- Smart phone compatible
- (1) Wireless wall button
- (2) Remote controls
- Wired Safety Beams
- Janus sheet door adapters

OPTIONAL ACCESSORIES:

- Wireless Keypad

Available for use on the 1950, 1950HD,
2000, 2500, 3000 and 5000 Series

COMMERCIAL DOOR OPENER

Discover how DBCI can provide the service, performance and reliability your project demands.

800-542-0501

dbci.com

WARRANTY

- 2 year/5,000 cycles on parts
- 1 year on accessories



The HIRO delivers you both control and connectivity via the in-built smartphone control system. Whether you have a very large roller door, a wind-locked door, or require low side room compatibility, the Hiro opener is the perfect choice for your commercial and industrial needs.

DBCI is a leading manufacturer of commercial-grade steel doors, components, and accessories.

TECHNICAL SPECIFICATIONS

Power	Input Voltage	120V a.c. / 60 Hz
	Motor Type	24V d.c. Permanent Magnet
	Current (max)	2A
	Short-Term Lifting Force	400N
Installation^{1,2}	Door Size	300 ft ²
	Door Size (wind-lock)	236 ft ²
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (434.37, 433.47 & 433.92MHz)
	Coding System	TrioCode™ 128, code hopping
	Code Combinations	3.4x10 ³⁸ code combinations
	Transmitter Type	TrioCode™ 128
	Transmitter Capacity (x 4-button registers)	64
Additional Features	Courtesy Light	LED
	Safety Beam Compatibility	2-wire Safety Beams
	Installation	Suits most sheet doors*
	Battery backup	Optional
Warranty³	"5 year/10,000 cycles on parts 1 year on accessories"	

* Please see full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under American Law.

1. Windy conditions can activate the obstruction feature of the opener.

2. Suitable for use on dead axle doors.